

7051

SUPERIOR

Wall Base Adhesive

1. PRODUCT NAME

ROBERTS® 7051 Wall Base Adhesive

2. MANUFACTURER

Roberts Company Canada, Ltd.
34 Hansen Road South
Brampton, ON L6W 3H4
(866) 435-8665 / (905) 791-4444

3. DESCRIPTION

ROBERTS 7051 is a superior performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base.

Features and Benefits

- High performance acrylic
- Extra high wet strength for bonding heavy rubber base
- Quick grabbing, fast set-up and solvent-free
- Enviro-Friendly – solvent-free and LEED® compliant; VOC < 1 g/L, SCAQMD Rule 1168
- GoldGuard® antimicrobial product protection

Uses

For adhering vinyl, rubber and carpet wall base, including 6" material.

Coverage and Trowel Options*

3/16" x 5/32"

Flooring: Wall Base (100 mm / 4")
Coverage: 122 lineal meters per 3.78 L / 400 lineal feet per gallon

1/8" x 1/8"

Flooring: Wall Base (100 mm / 4")
Coverage: 100 lineal meters per 3.78 L / 400 lineal feet per gallon

Snozzle

Flooring: Wall base (100 mm / 4")
Coverage: 15-18 lineal meters per 887 mL / 50-60 lineal feet per 30 oz

**The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.*

Limitations

- For interior installations only.
- Ensure adequate ventilation during installation.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.

4. TECHNICAL DATA

Product Type:	SBR Acrylic Latex
Color:	Off-white
Odor:	Very mild; odorless when dry
Open Time:	Up to 10 minutes
Working Time:	Up to 30 minutes
VOC:	< 1 g/L
PH:	Must not exceed 9.0
Shelf Life:	1 year in unopened container
Storage:	Freeze-thaw stable to -12°C/10°F



5. INSTRUCTIONS

Preparation

Ensure substrate, wall base material and adhesive are fully acclimated prior to installation at the same temperature and humidity level expected during normal use (between 18-35°C/65-95°F) with a relative humidity (RH) of no greater than 65%. Maintain these conditions after the installation.

Surface must be structurally sound, dry, smooth, flat, free of excess moisture/alkali and all substances (paint, wall coverings, dust, etc.) that might interfere with the performance of the wall base or its installation.

For best results, wrapped or rolled wall base should lay flat for 24 hours before application and the back of the wall base should be wiped with mineral spirits for maximum adhesion.

Installation

Materials and area temperature must be between 18-35°C/65-95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation.

Trim any vinyl wall coverings to 1/4" below the top of the wall base with a ROBERTS Knife. Apply adhesive uniformly to the wall or to the back of the wall base. Press the wall base firmly in place while the adhesive is still wet (typically within 10 minutes).

Use the ROBERTS Hand Roller to press and smooth wall base into the adhesive. Always roll back to the starting point to prevent stretching the adhesive.

Curing

8-10 hours. High temperature and low humidity will cause the adhesive to cure faster.

Clean-up

Fresh adhesive – warm, soapy water.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

6. AVAILABILITY

Packaging

10 L / 2.6 U.S. gallon Plastic Pail	7051RB010	075378705130
3.78 L / 1 U.S. gallon Plastic Pail	7051RB004	075378705116
887 mL / 30 U.S. ounce Tube	7051RB852	075378705178

7. WARRANTY

10-Year Direct Bond

ROBERTS warrants that this product will be free from manufacturing defects for 12 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. ROBERTS will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9



ROBERTS®, GoldGuard®, and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® and is used with permission.

11179