

8502

PREFERRED

Latex Carpet Seam Sealer

1. PRODUCT NAME

ROBERTS® 8502 Latex Carpet Seam Sealer

2. MANUFACTURER

Roberts Company Canada, Ltd.

34 Hansen Road South
Brampton, ON L6W 3H4
(866) 435-8665 / (905) 791-4444

3. DESCRIPTION

ROBERTS 8502 Latex Carpet Seam Sealer is recommended for seam sealing carpets, sealing raw edges, binding, strengthening worn backings and applying new backings on area rugs. ROBERTS 8502 may also increase slip resistance on mats or rugs. ROBERTS 8502 contains UV tracers for easy detection.

Features and Benefits

- Seals and binds carpet edges to prevent raveling
- Contains UV tracers for easy detection
- Use to apply new backings to area rugs
- Provides enhanced slip resistance
- Enviro-Friendly – solvent-free and LEED® compliant; VOC < 1 g/L
- CRI Green Label Plus® Certified – GLP #34711

Uses

For sealing raw edges, binding, strengthening worn backings and applying new backings on area rugs. It may also be used to increase slip resistance on mats or rugs.

Coverage

Up to 725 lineal feet per U.S. quart / 221 lineal meters per 946 mL.

Limitations

- Be careful not to get sealer on rug surface.
- Ensure adequate ventilation during flooring installation.
- Not recommended for sealing urethane, vinyl-backed carpets or sheet goods.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards and manufacturer's guidelines and specific recommendations prior to installation for additional information.

4. TECHNICAL DATA

Product Type: Acrylic Latex

Colour: Off white

Odour: Very mild, odourless when dry

Open Time: Up to 10 minutes

VOC: < 1 g/L

Shelf Life: 1 year in unopened container

Storage: Protect from freezing. Does not require thinning.

5. INSTRUCTIONS

Installation

Conventional and Double Glue Installations— Prepare and cut carpet edges according to manufacturer's recommendation. Apply a 1/8" (3mm) bead of adhesive to both sides of the carpet along the backing where the face yarns enter the backing (not the cushion) with an applicator bottle.

Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap. Allow adhesive to become dry to the touch before joining the seams with a carpet seam tape.

Refer to CRI 104 and 105 Installation Standards for additional information.

Clean-up

Within 10 minutes after seaming carpet use warm, soapy water or mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING. USING TOO MUCH CLEANER CAN CAUSE PERMANENT DAMAGE AND TEMPORARY SWELLING OF THE CARPET.** Remove any traces of adhesive on unwanted areas of the carpet. Ensure there is no excess adhesive left on the face of the yarn that can eventually attract dirt.



6. AVAILABILITY

Packaging

946 mL / 1 U.S. quart Tube	8502RB001	075378000372
----------------------------	-----------	--------------

7. WARRANTY

5-Year Direct Bond

ROBERTS warrants that this product will be free from manufacturing defects for 12 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. ROBERTS will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc.
CRI Green Label +PLUS® is a registered trademark of The Carpet and Rug Institute • LEED®, and its related logo, is a trademark owned by the U.S. Green Building Council® and is used with permission.

11178