

5505

SUPERIOR

Urethane Adhesive Remover

1. PRODUCT NAME

Roberts® 5505 Urethane Adhesive Remover

2. MANUFACTURER

Roberts Consolidated Industries, Inc.

300 Cross Plains Blvd
Dalton, GA 30721
(866) 435-8665 / (706) 277-5294

3. DESCRIPTION

Roberts 5505 Urethane Adhesive Remover is a superior adhesive remover to aid in the removal of adhesive from flooring surfaces and tools.

Features and Benefits

- Quick and easy adhesive spot removal
- Extremely low odor
- Wipes are biodegradable
- Advanced technology formula

Uses

For the removal of fresh and recently cured urethane from pre-finished (non-wax) wood flooring, and the removal of fresh and recently cured 2-part epoxy, PVA (carpet seam sealers, carpet and wood) and SBR (multipurpose, carpet and VCT) adhesives.

Limitations

- Ensure adequate ventilation during flooring installation.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards and manufacturer's guidelines and specific recommendations prior to use for additional information.

4. TECHNICAL DATA

Product Type:	Liquid/Wipe
Color:	Clear
Odor:	Sharp
VOC:	< 500 g/L
Shelf Life:	1 year in unopened container
Storage:	Protect from freezing. Does not require thinning.

5. INSTRUCTIONS

Installation

Test 5505 in an inconspicuous area prior to use. Remove adhesive while it is fresh for best results. The chemical composition of adhesives can vary greatly. Some reactive adhesives are difficult to remove once fully cured.

Wet Spot Removal— Apply 5505 to a clean, white cloth and rub adhesive lightly to remove. Clean surface with a suitable floor cleaner and wipe dry.

Dry Spot Removal— Allow 5505 to saturate adhesive (approx. 1 hr.) to soften. Light spots and fingerprints: Use 5505 and remove spot using a Magic Eraser®. Clean surface with a suitable floor cleaner and wipe dry. Heavy spots: First remove softened adhesive with plastic putty knife, then use melamine pad (cleaning eraser) to remove any remaining residue. Clean surface with a suitable floor cleaner and wipe dry.

NOTE— The chemical composition of adhesives can vary greatly. Some reactive adhesives are difficult to remove once fully cured. It is always best to remove adhesives immediately while they are fresh. Do not scrub surface of wood aggressively as this may damage the surface.

6. AVAILABILITY

Packaging

24 ounce Plastic Bottle (710 mL)	5505	075378550525
60 Towelettes	5505-W	075378550563

7. WARRANTY

Roberts warrants that this product will be free from manufacturing defects for 12 months from the date of purchase, when applied in accordance with Roberts' instructions and industry standards. Roberts' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. Roberts will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9





Roberts® is a registered trademark of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc.

9893