

2072

SUPERIOR

Linoleum Adhesive

1. PRODUCT NAME

ROBERTS® 2072 Linoleum Adhesive

2. MANUFACTURER

Roberts Company Canada, Ltd.
34 Hansen Road South
Brampton, ON L6W 3H4
(866) 435-8665 / (905) 791-4444

3. DESCRIPTION

ROBERTS 2072 is a superior, commercial-grade adhesive designed specifically for the installation of linoleum flooring. This adhesive is designed with an early strength to grab and hold stiff linoleum floors in place.

Features and Benefits

- Strong initial grab
- Low odour
- Great working time
- Enviro-Friendly – solvent-free and LEED® compliant; VOC 6 g/L
- CRI Green Label Plus® Certified – GLP #36471
- GoldGuard® antimicrobial product protection
- Traffic – Heavy Commercial

Uses

For the interior installation of linoleum flooring.

Coverage and Trowel Options*

3/32" x 3/32" x 3/32"

Flooring: Linoleum

Coverage: 46.5-18.9 m² per 18.19 liters / 500-600 ft² per 5 gallons

**The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.*

Substrates

Concrete, CANPLY/APA underlayment rated plywood, vinyl composition tile (clean, free of wax), primed gypcrete (refer to ASTM F2419), non-cushioned paper-backed sheet goods (properly prepared with embossing leveler), radiant heated floors and terrazzo.

Limitations

- Ensure substrate, flooring material and adhesive are fully acclimated prior to installation at the same temperature and humidity level expected during normal use (between 18-35°C/65-95°F with a relative humidity (RH) of no greater than 65%).
- Ensure adequate ventilation during installation.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.

4. TECHNICAL DATA

Product Type: Acrylic Latex

Colour: Off-white

Odour: Neutral

Open Time: Up to 45 minutes

Working Time: Up to 25 minutes

VOC: 6 g/L

pH: Must not exceed 10

Shelf Life: 1 year in unopened container

Storage: Protect from freezing. Does not require thinning.

5. INSTRUCTIONS

Preparation

Subfloors must be structurally sound, dry, smooth, flat ($\leq 3/16"$ within 10'), level and free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring or its installation.

All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Expansion or other moving joints must not be filled or covered with flooring. Patching compounds must be suitable for the use application, cement based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

Materials and area temperature must be between 18-35°C/65-95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Lift a corner periodically to ensure 100% coverage of adhesive to the flooring backing and the substrate to ensure a void free bond.

Spread adhesive uniformly. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the back of the linoleum flooring. Place linoleum into the adhesive while the adhesive is still fresh. The amount of time in which you have to place the flooring will vary with temperature and humidity.



Clean-up

Fresh adhesive – warm, soapy water.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth.
DO NOT POUR DIRECTLY ONTO FLOORING.

6. AVAILABILITY

Packaging

18.19 L / 5 U.S. gallon Plastic Pail	2072RB020	075378207252
--------------------------------------	-----------	--------------

7. WARRANTY

10-Year Direct Bond

ROBERTS warrants that this product will be free from manufacturing defects for 12 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to one year. ROBERTS will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9



ROBERTS®, GoldGuard®, and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc.
CRI Green Label +Plus® is a registered trademark of The Carpet and Rug Institute • LEED®, and its related logo, is a trademark owned by the U.S. Green Building Council® and is used with permission.

11181