70-175

Natural Cork Underlayment Sheets



FEATURES & BENEFITS:

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Use under ceramic tile, stone, marble, glued wood flooring and floating floor systems
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and loosely configurations
- Use Roberts 7350 Adhesive for double glue down applications

Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

Acoustical Performance	STC	IIC	R-Value**	Single Sheet: 2' x 3'
6 mm (1/4") Cork Underlayment Sheets				
With 6" cement slab	52	51	0.75	50 sheets/case
With 6" cement slab & suspended ceiling	60	61	0.75	Coverage: 300 ft²/case

****R-Value -** Rating used to measure resistance to heat flow.

S0215-9493

Quality & Excellence Since 1938.

www.ROBERTSCONSOLIDATED.com

U.S. Headquarters	Canada	Europe/Middle East	Australia	New Zealand
866 435 8665	800 840 9422	0031 24 6485348	011 61 3 9797 1888	64 9 415 9700