

Latex Carpet Seaming Adhesive



Environmentally safe · Non-flammable



ROBERTS® 8502 Latex Carpet Seaming Adhesive is recommended for seaming polypropylene, jute, latex unitary and woven backed carpet edges. Prevents unraveling and/or delamination of carpet backings and yarns. For binding, sealing raw edges and applying new backings to area rugs. ROBERTS **8502 IS NOT RECOMMENDED**

FOR SEAMING URETHANE, VINYL BACKED CAR-PETS OR SHEETGOODS.

TYPICAL PROPERTIES:

Appearance: White **Base: Natural Latex** Non-volatiles: 51%

Consistency: Pourable Cream

Shelf-Life: One year minimum at 70°F

Flash Point: Non-Flammable Open Time: Up to 10-15 minutes Coating VOC: 23 grams/liter

Ventilation: Implement effective ventilation before, during and after installation by opening windows and doors for an adequate supply of fresh air. Consider using window fans and/or air movers to bring in fresh air and enhance the curing time of the sealer.

Preparation & Application:

- Roberts 8502 adhesive is NOT freeze-thaw stable. Do not allow the adhesive to freeze.
- The Roberts 8502 adhesive and substrate must be at least 65°F (18.3°C) or higher if recommended by the flooring manufacturer.
- Prepare and cut the carpet edges according to the manufacturer's recommendations.

Conventional and Double Glue Installation:

- Apply a 1/8" bead of adhesive to **BOTH** sides of the carpet along the backing and where the face yarns enter the backing (not the cushion) with a Roberts 10-145 Applicator Bottle. Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap.
- Allow the adhesive on both edges of the carpet to become dry to the touch before joining the seam.
- Refer to CRI 104-105 installation standards for additional information.

Clean Up: Within 10 minutes after using the Roberts 8502 Latex Carpet Seaming Adhesive, use Roberts 1912 Adhesive Cleaner sparingly, with a clean white cotton cloth, to completely remove any traces of sealer on the carpet surface and wipe clean all seams to ensure that there is no excess sealer left on the face of the varn that can eventually attract dirt. DO NOT POUR CLEANER DIRECTLY ONTO FLOORING. USING TOO MUCH CLEANER CAN **CAUSE PERMANENT DAMAGE AND TEMPORARY SWELLING OF THE CARPET.**

Warranty: Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Any implied warranty of merchantability or fitness for particular use is limited to one year from date of purchase. Liability for any incidental or consequential damage or loss is specifically excluded at all times. If used for other than professional purposes, any implied warranty of merchantability or fitness for particular use is excluded.

First Aid:

Skin Contact: Remove fresh adhesive with warm

water and soap. Consult physician if

irritation develops.

Eye Contact: Flood with large quantities of water

for 15 minutes. See physician if

irritation develops.

Ingestion: Do not enduce vomiting. If victim is

conscious, give water to dilute. Contact a physician immediately.

KEEP OUT OF REACH OF CHILDREN.

Rated for commercial or residential use.

Refer MSDS for more information.

Made in Canada

Available in these sizes:







8502-0