

70-175

Natural Cork Underlayment Sheets

FEATURES & BENEFITS:

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Use under ceramic tile, stone, marble, glued wood flooring and floating floor systems
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and looselay configurations
- Use Roberts 7250 Adhesive for a single glue down application to the subfloor and Roberts 1407 Adhesive for double glue down applications



Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

Acoustical Performance

STC

IIC

R-Value**

Single Sheet: 2' x 3'

6 mm (1/4") Cork Underlayment Sheets

With 6" cement slab	52	51	0.75
With 6" cement slab & suspended ceiling	60	61	0.75

50 sheets/case
Coverage: 300 ft²/case

**R-Value - Rating used to measure resistance to heat flow.

S0215-9493

Quality & Excellence Since 1938.

www.ROBERTSCONSOLIDATED.com

U.S. Headquarters
866 435 8665

Canada
800 840 9422

Europe/Middle East
0031 24 6485348

Australia
011 61 3 9797 1888

New Zealand
64 9 415 9700