



7200HP

HIGH-PERFORMANCE BASE BOND® Wall Base Adhesive

1. PRODUCT NAME

ROBERTS® 7200HP HIGH-PERFORMANCE BASE BOND®

Wall Base Adhesive

2. MANUFACTURER INFORMATION

Roberts Consolidated Industries, Inc.

300 Cross Plains Blvd
Dalton, GA 30721
(866) 435-8665 / (706) 277-5294

3. DESCRIPTION

ROBERTS® 7200HP HIGH-PERFORMANCE BASE BOND® is a superior-grade, solvent-free adhesive specifically designed for the interior installation of vinyl, rubber and carpet wall base. The tenacious wet-suction capabilities this formula offers make it ideal for use over porous wall surfaces such as gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete. VOC < 1 g/L.

Features and Benefits

- Excellent holding power and great wet suction
- Fast set-up and non-staining formula
- Strong initial grab for holding wall base
- Outstanding plasticizer migration resistance
- Enviro-Friendly – solvent-free and LEED® compliant; VOC < 1 g/L, SCAQMD Rule 1168
- CRI Green Label Plus® Certified
- GoldGuard® antimicrobial product protection

Meets Environmental Standards

LEED® EQc 4.1 (100 g/L limit)	SCAQMD, Rule 1168 (100 g/L limit)
PASSES	PASSES

Uses

For adhering vinyl, rubber and carpet wall base.

Coverage and Trowel Options*

	Snozzle Flooring: Wall base (4") Coverage: Up to 60 linear ft. per 30 oz 2.3 or 5-hole applicator nozzle Coverage: Up to 70 linear ft. per 30 oz
	1/8" x 1/8" x 1/8" SQ-Notch Flooring: Wall Base (4") Coverage: Up to 240 linear ft. per gallon
	3/16" x 5/32" V-Notch Flooring: Wall Base (4") Coverage: Up to 150 linear ft. per gallon

*The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.



Substrates

Porous wall surfaces such as gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete.

Limitations

- ROBERTS 7200HP HIGH-PERFORMANCE BASE BOND® is not recommended over non-porous materials or painted surfaces.
- For interior installations only.
- Concrete and plaster must be properly seasoned and dry prior to installation.
- Ensure adequate ventilation during installation.
- Refer to ROBERTS 7200HP HIGH-PERFORMANCE BASE BOND® Safety Data Sheet, robertsconsolidated.com, industry standards, and manufacturer's specific guidelines and recommendations (prior to installation) for additional information.

4. TECHNICAL DATA

Product Type:	Acrylic Polymer Paste
Color:	Creamy Tan
Odor:	Mild, sweet odor; odorless when dry
Open Time:	Up to 10 minutes
Working Time:	Up to 30 minutes
VOC:	< 1 g/L
pH:	7-10
Shelf Life:	2 years when stored in unopened package at (50°F-85°F)
Storage:	Protect from freezing

5. INSTRUCTIONS

Preparation

30 oz. cartridge – Unscrew cap, cut top seal and load into closed barrel gun or open barrel skeleton gun. Squeeze gun gently, with even pressure, to apply.

11 oz. Cartridge – Cut tip, load into 11oz. closed barrel gun or open barrel skeleton gun. Squeeze gun gently, with even pressure, to apply.

Available accessory: ROBERTS® 10-981-25 SNOZZLE

Substrate must be clean, dry and free of contaminants including paint. If the back of the wall base material is soiled prior to installation, clean with a cloth dampened with a mild soap and water solution, rinse and dry.

Installation

Maintain a consistent and ambient relative humidity before, during and after installation (between 65-85° F with a maximum RH of 65%). Follow the wall base manufacturer's guidelines for layout and design. Apply adhesive to the back of the wall base with appropriate applicator or 1/8" notch trowel to ensure 90% coverage of adhesive while not spreading within ¼" from the top of the wall base. Observe the appropriate open time. While the adhesive is still fresh, press the wall base firmly in place. Be careful not to stretch the wall

base during the application process. Use a hand roller to ensure a secure and void-free bond between the wall base and the substrate. Roll the wall base in the direction of the last piece installed to ensure a tight seam.

Open Time: Up to 10 minutes **Working Time:** Up to 30 minutes

Curing

24 hours. High temperature and low humidity will cause the adhesive to cure faster.

Clean-up

Fresh adhesive – warm, soapy water on a clean cloth.

Dried adhesive – mineral spirits sparingly on a clean, cotton cloth.

Do Not pour cleaning agent directly onto wall base.

6. AVAILABILITY

Packaging

4 gallon Plastic Pail (15.14 L)	7200-HP4	075378720157
1 gallon Plastic Pail (3.78 L)	7200-HP1	075378720140
30 ounce Tube (887 mL)	7200-HP30	075378720133
11 ounce Tube (325 mL)	7200-HP11	075378720164

7. WARRANTY

ROBERTS® warrants that this product will be free from manufacturing defects for 24 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.** Any implied warranties arising by operation of law are limited to two years. ROBERTS will not be liable for any incidental or consequential damages.

Visit robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9



ROBERTS®, BASE BOND® are trademarks of Roberts Consolidated Industries, Inc., GoldGuard®, and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. CRI Green Label +Plus® is a registered trademark of The Carpet and Rug Institute • LEED®, and its related logo, is a trademark owned by the U.S. Green Building Council® and is used with permission.

50623-12195