

Safety Data Sheet Revision Date: 09/13/2023

SECTION 1:

Identification and Company Details

| Product Name: | 3095 HIGH-PERFORMANCE CARPET ADHESIVE Residential & Commercial |
|--|--|
| Product Code: | 3095 |
| Manufacturer/ Supplier: | Roberts Consolidated Industries, Inc. |
| Address: | 300 Cross Plains Blvd. |
| | Dalton, GA 30721 |
| Emergency Phone: | (800) 424-9300 (24-hour Response / CHEMTREC) |
| Product Information: | (706) 277-5294 |
| Recommended Use: | Adhesive |
| Emergency Phone: Product Information: | Dalton, GA 30721 (800) 424-9300 (24-hour Response / CHEMTREC) (706) 277-5294 |

SECTION 2: Hazard(s) Identification

| OSHA / HCS Status: Classification of the | This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) |
|---|---|
| substance or mixture: | Skin corrosive- Category 2 |
| | Respiratory sensitizer- Category 1 |
| | Skin irritant- 1 |
| Signal Word: | Danger |
| Hazard Statements: | May cause an allergic skin reaction |
| | May cause allergy or asthma symptoms or breathing difficulties if inhaled |
| | Causes skin irritation |
| | |
| | |
| Hazard Pictograms: | \mathbf{V} |
| Precautionary | |
| Statements: Obtain specia | al instructions before use |
| | Do not handle until all safety precautions have been read and understood |
| | Keep container tightly closed |
| | Use personal protective equipment as required |
| | IF ON SKIN: Wash with soap and water |
| | IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing |
| | IF exposed or concerned: Get medical advice/ attention |
| | If irritation or a rash occurs: Get medical advice/ attention |
| | Store locked up |
| | Store in a well ventilated place. Keep container tightly closed and cool. |
| | Dispose of contents/ container in accordance with local authority requirements. Incineration is the preferred method of disposal. |
| | |

SECTION 3: **Composition / Information on Ingredients**

| | Weight % | CAS # | |
|------------------|----------|------------|--|
| Naphthenic Oli | 19.0% | 64742-52-5 | |
| Urea | 2.0% | 57-13-6 | |
| Quartz | 0.9% | 14808-60-7 | |
| Titanium Dioxide | 0.6% | 13463-67-7 | |

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding. During normal usage of the product as recommended, airborne dusts will not be present.

SECTION 4: First-Aid Measures

| Inhalation: | Move victim to fresh air. Consult physician if necessary. |
|--------------------|--|
| Skin Contact: | Wash with soap and water. Remove contaminated clothing. Consult physician if necessary. |
| Eye Contact: | Flush with copious amounts of water for at least 15 minutes. Consult physician if necessary. |
| Ingestion: | Do not induce vomiting. Wash mouth with water. Consult physician. |
| Note to Physician: | Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation. Skin: |
| | Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn. Ingestion: |
| | Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. |
| | Respiratory: Treatment is essentially symptomatic. Remove individual with symptoms from exposure and assist in breathing if necessary. |

SECTION 5: Fire-Fighting Measures

Extinguishing Media: This product is not flammable. Use fire- extinguishing media appropriate for surrounding materials. **Hazardous Combustion Products:** No particular hazards known.

Protection of Firefighters: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6: Accidental Release Measures

| Personal Precautions: | Use protective gloves, goggles and suitable protective clothing. |
|-----------------------|--|
| | Do not allow product to get into drains, soil, or surface water. Small Spillages: Absorb with sand or other inert absorbent. Large Spillages: Dam and absorb spillages. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Wear necessary protective equipment. |
| SECTION 7: Handlin | g and Storage |
| Handling Precautions: | Provide good ventilation. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. |
| Storage: | Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store in closed original container at temperatures between 5°Cand 30°C/ 40°F and 86°F. Protect from freezing and direct sunlight. |
| SECTION 8: Exposu | re Control / Personal Protection |

| Exposure Guidelines: | Not determined | | | |
|--------------------------------|-------------------------------|--|--|--|
| Engineering Controls: | Provide adequate ventilation. | | | |
| Personal Protective Equipment: | | | | |

Skin Protection - Permeation resistant gloves (butyl rubber, nitrile rubber, PVC or polyvinyl alcohol). *Eye/Face Protection* - Glasses with side shields, chemical splash goggles and/or face shield.

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|------------------------------|---------------------------|-----------------------|-----------------------|
| Naphthenic Oil/ 64742-52-5 | Not Established | Not Established | Not Established |
| Urea/ 57-13-6 | Not Established | Not Established | Not Established |
| Quartz/ 14808-60-7 | Not Established | 0.025 mg/m3 | NIOSH: 0.05 mg/m3 TWA |
| | | (respirable fraction) | (respirable dust) |
| Titanium Dioxide/ 14808-60-7 | 15 mg/m3 TWA (total dust) | 10 mg/m3 TWA | Not Established |
| | | | |
| | | | |
| | | | |
| | | | |

| Appearance: | Heavy beige paste | | |
|---|---|--|--|
| Odor: | Very mild, non- offensive odor | | |
| Relative Density: | 1.24 | | |
| Odor Threshold: | Not available | | |
| Solubility: | Miscible in water | | |
| pH: | 9.80 | | |
| Partition Coefficient: | n-octanol/water; Not determined | | |
| Melting Point: | Not determined | | |
| Freezing Point: | Not determined | | |
| Auto-ignition Temperature: Not determined | | | |
| Flash Point: | Non- flammable > 204 C (400 F) Cleveland Closed Cup | | |
| Decomposition Temperature: Not determined | | | |
| Evaporation Rate: | Not determined | | |
| Viscosity: | Not determined | | |
| Flammability (Solid/Gas): | Not applicable | | |
| Upper/Lower Flammability: Not determined | | | |
| VOC Content: | <1 g/L | | |
| Vapor Pressure: | Not Determined | | |
| Boiling Point: | 100°C/ 212°F | | |

SECTION 10: **Stability and Reactivity**

| Chemical Stability: | Stable under normal temperature conditions and recommended use. |
|----------------------|---|
| Conditions to Avoid: | Excessive heat, direct sunlight and/or frost. |
| Materials to Avoid: | None. |

SECTION 11: **Toxicological Information**

| Mixture Toxicity: Acute toxicity: | Inhalation Toxicity LC50: 98mg/L | | |
|--------------------------------------|----------------------------------|---------|--|
| Ingestion: | Not determined | | |
| Inhalation: | Not determined | | |
| Skin Contact: | Not determined | | |
| | CAS Number | %Weight | |
| Titanium Dioxide | 13463-67-7 | 0.6 | |
| Quartz | 14808-60-7 | 0.9 | |
| SECTION 12: Ecological Information | | | |

Mobility and Bioaccumulation Potential: Not determined Degradation: Not determined Aquatic Toxicity: Not determined LC50 – 24 hour (Static): Not determined Component Ecotoxicity: Naphthenic Oil 96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L

Urea

96 Hr LC50 Poecilia reticulata: 16200 - 18300 mg/L

48 Hr EC50 Daphnia magna: 3910 mg/L [Static]

SECTION 13: **Disposal Considerations Disposal:** Dispose of waste and residues in accordance with local authority requirements. Incineration is the preferred method of disposal. Same as above.

Wastes or Residues:

SECTION 14: Transport Information

| Road: | DOT Proper Shipping Name: Non-Regulated | | |
|--------|---|--|--|
| | DOT Packing Group: N/A | | |
| | DOT Label: N/A | | |
| | UN Number: N/A | | |
| Ocean: | Proper Shipping Name: Non-Regulated | | |
| | Sea – IMO/IMDG Class: N/A | | |
| | UN Number: N/A | | |
| | Label: N/A | | |
| | Packing Group: N/A | | |
| | Marine Pollutant: N/A | | |
| | EMS: N/A | | |
| Air: | Proper Shipping Name: Non-Regulated | | |
| | Air – ICAO/IATA Class: N/A | | |
| | UN Number: N/A | | |
| | Label: N/A | | |
| | Sub Class: N/A | | |
| | Packing Group: N/A | | |
| | Pack Instr. Passenger: N/A | | |
| | Pack Instr. Cargo: N/A | | |
| | | | |

SECTION 15: Regulatory Information

Status on Substance Lists: The concentrations shown in this document are maximum levels (weight %) to be used for regulations.

| TSCA: | The components of this product are contained on the chemical substance inventory list | | | | |
|--------------|--|---|-----------------------|-------------------------|----|
| IARC: | Not carcinogenic | | | | |
| OSHA PEL's | None | | | | |
| Federal EPA: | Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): Requires notification of the national response center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at level which could require reporting under the statute are: | | | | |
| | Chemical Name | CAS Number | % by Weight | RQ | |
| | None Superfund Amendments an emergency planning based Reportable Quantities (RQ require reporting under this | d on Threshold Planning) in 40 CFR 355. Compo | Quantities (TPQs) and | release reporting based | on |
| | Chemical Name | CAS Number | % by Weight | RQ | |
| | None | None | None | None | |
| | Section 311-312 require p identified and made known NJ RTK 13463-67-7 Titanium Dioxi 14808-60-7 Quartz 1332-58-7 Inert Filler Pennsylvania RTK 13463-67-7 Titanium Dioxi 14808-60-7 Quartz 1332-58-7 Inert Filler 8050-09-7 Rosin SARA 302 Extremely Ha: Massachusetts RTK 13463-67-7 Titanium Dioxi 14808-60-7 Quartz 1332-58-7 Inert Fill EPA Hazard Classificatio | ι. de de zardous Substances - Ν de | | | |

| Acute | Chronic | Fire | Pressure | Reactive |
|--------|---------|--------|----------|----------|
| Hazard | Hazard | Hazard | Hazard | Hazard |
| Yes | No | No | No | No |

Section 313 requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all SDSs that are distributed for this material. Components present in this product at level which could require reporting under the statute are: **None** All components are on the DSL list or exempt.

Canada DSL:

California Proposition 65: Does not contain any listed chemical to the best of our knowledge.

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

HMIS RATING: HEALTH-1, FLAMMABILITY-0, REACTIVITY-0, PERSONAL PROTECTION- B.

Prepared by: Roberts Consolidated Product Safety & Regulatory Compliance Group, (706) 277-5294

The information herein is given in good faith, but no warranty expressed or implied is made. Roberts Consolidated urges users of this product to evaluate its suitability and compliance with local regulations as Roberts Consolidated cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 09/13/2023