

# AcoustiShield™ UNDERLAYMENT

70-113

## Superior IIC Sound Ratings for LVP Underlayment

### PROTECTION

Includes adhesive strip for easy installation and overlap film to seal out moisture

### ANTIMICROBIAL

Dense foam structure offers advanced mold and mildew protection

### LONG LASTING

Exceptional compression strength protects your floor's tongue and groove system

**IIC** **STC** **Δ**  
**71** | **65** | **24**

### VERSATILE

Compatible for use under laminate, engineered wood, LVP / LVT, engineered vinyl plank, SPC and WPC

### SPECIFICATIONS

ITEM #	70-113
UNIT OF MEASURE	19 ROLLS / CASE
COVERAGE	100 SQ. FT. / ROLL 1900 SQ. FT. / CASE
WIDTH OF ROLL	48"
LENGTH OF ROLL	25' (300")
THICKNESS	1 MM
WEIGHT PER ROLL	1.92 lbs
DIAMETER OF ROLL	4.875"



\*IIC measures sound such as moving furniture and walking, STC measures sound such as voices and television. Minimum IIC and STC sound rating requirement is 50 according to the International Building Code. Δ Delta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

Scan here for  
PRODUCT  
INFORMATION



ROBERTS® AcoustiShield™ premium LVP underlayment's unique crosslinked polypropylene foam technology provides superior sound ratings. In addition to its superior compression strength, moisture resistance and mold / mildew defense, AcoustiShield has exceptional structural integrity and stability providing flat placement, straight corners and crisp edges to help ensure a successful installation for the life of your floors.